



REVISION RECORD				
REV	ECN.	DESCRIPTION	DRFT	DATE

**NOTE 1:**  
**UL标准 (UL Standard)**  
 1. 额定电压与电流: 300V/10A  
 Rated voltage/Rated current: 300V/10A  
 2. 功耐电压: AC1000V/Min  
 Withstanding Voltage: AC1000V/Min  
 3. 线径范围: 22~16AWG  
 Wire range: 22~16AWG  
**IEC标准 (IEC Standard)**  
 1. 额定电压与电流: 250V/17.5A  
 Rated voltage/Rated current: 250V/17.5A  
 2. 线径范围: 1.5mm<sup>2</sup>  
 Wire range: 1.5mm<sup>2</sup>

**NOTE 2:**  
 1. 间距 (Pitch): 6.35mm  
 2. 使用温度范围: -40℃~+105℃  
 Operating temperature: -40℃~+105℃  
 3. 符合RoSE环保要求  
 RoSE Compliance  
 4. 额定扭矩: 3.54 [Lb. in]  
 (Rated torque): 3.54 [Lb. in]  
 5. 未标注公差表  
 Undimensioned tolerances

开槽方向公差 (mm)		其他尺寸公差 (mm)					0.1/10			
Pitch range in mm	Nominal dimension range in mm	≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60		60 ~ 100	100 ~ 150	> 150
≤6	6 ~ 10	±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00	±1'

**订购方式 (HOW TO ORDER)**  
**HB635M - 6.35 - □ - P - □ - □ - □ - □ - □**

型号 (Series NO.)    间距 (Pitch)    极数 (Poles)    客户型号 (Customer Request)

**颜色 (Color):**  
 1. 灰色 (Gray)    2. 蓝色 (Blue)  
 3. 黑色 (Black)    4. 绿色 (Green)  
 5. 橙色 (Orange)    6. 红色 (Red)  
 7. 黄色 (Yellow)    8. 白色 (White)  
 9. 透明 (Transparent)

3	(Contact)触点	(Copper alloy)铜合金	(Sn plated)镀锡
2	(Screw)螺丝 M2.5	(Steel)钢	(Ni plated)镀镍
1	(Housing)罩件	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

PART NO.: /

APPD: /

CHKD: /

DRFT: /

THIRD ANGLE PROJECTION

**宁波迈科思电子科技有限公司**  
 NINGBO MAX ELECTRONIC TECHNOLOGY CO.,LTD

型号: HB635M-6.35-XXP  
 系列: HB635M-6.35  
 图号: HB635M635001

页码: 1/1  
 比例: 1:1