

REVISION RECORD			
REV	ECN.	DESCRIPTION	DATE

NOTE 1:
UL标准 (UL Standard)

1. 额定电压与电流: 300V/20A
Rated voltage/Rated current: 300V/20A
2. 功额定: AC1600V/Min
Withstanding Voltage: AC1600V/Min
3. 线径范围: 28~12AWG
Wire range: 28~12AWG

IEC标准 (IEC Standard)

1. 额定电压与电流: 250V/20A
Rated voltage/Rated current: 250V/20A
2. 线径范围: 2.5mm²
Wire range: 2.5mm²

NOTE 2:

1. 间距 (Pitch): 5.08mm
2. 使用温度范围: -40℃~+105℃
Operating temperature: -40℃~+105℃
3. 引线长度: 6~7mm
Stripping length: 6~7mm
4. 符合RoHS环保要求
RoHS Compliance
5. 额定扭矩: 0.05N·m 4.43 [Lb. in]
(Rated torque): 0.05N·m 4.43 [Lb. in]
6. 未标注公差按
Unlabeled tolerance

间距公差 (mm)		名义尺寸公差 (mm)	
Pitch range in mm		Nominal dimension range in mm	
≤6	6 ~ 10	30	60
10 ~ 24	10 ~ 24	60	100
		100	150
		150	≥
0.1/10	0.1/10		
≤	≤		
±1°	±1°		