



REVISION RECORD				
REV	ECN.	DESCRIPTION	DRFT	DATE

NOTE 1:
UL标准 (UL Standard)
 1. 额定电压与电流: 300V/15A
 Rated voltage/Rated current: 300V/15A
 2. 功率耐压: AC1000V/Min
 Withstanding Voltage: AC1000V/Min
 3. 线径范围: 28~12AWG
 Wire range: 28~12AWG
IEC标准 (IEC Standard)
 1. 额定电压与电流: 320V/10A
 Rated voltage/Rated current: 320V/10A
 2. 线径范围: 2.5mm²
 Wire range: 2.5mm²

NOTE 2:
 1. 间距 (Pitch): 5.00mm
 2. 使用温度范围: -40℃~+105℃
 Operating temperature: -40℃~+105℃
 3. 剥线长度: 7~8mm
 Stripping length: 7~8mm
 4. 符合RoHS环保要求
 RoHS Compliance
 5. 额定扭矩: 0.4N.m 3.54 [Lb. in]
 (Rated torque): 0.4N.m 3.54 [Lb. in]
 6. 未标注公差表
 Undimensioned tolerances

理方向公差 (mm)		其他尺寸公差 (mm)				D	D
Pitch range in mm	Nominal dimension range in mm						
≤6	≤30	30	60	100	150	≥	0.1/10
~10	~24	~60	~100	~150	~150	<	
±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00
							±1'

订购方式 (HOW TO ORDER)
MX2EDGKA-5.00 □ □ P □ □ □ □ □ □ □ □ □ □

型号 **间距** **极数** **客户型号**
Series No. **Pitch** **Poles** **Customer Request**

颜色 (Color)
 1. 灰色 (Gray) 2. 蓝色 (Blue)
 3. 黑色 (Black) 4. 绿色 (Green)
 5. 橙色 (Orange) 6. 红色 (Red)
 7. 黄色 (Yellow) 8. 白色 (White)
 9. 透明 (Transparent)

1. 单间距
Single Pitch
2. 双间距
Double Pitch

4	(Cage) 方盒	(Copper alloy) 铜合金	(Ni plated) 镀镍
3	(Contact) 触点	(Copper alloy) 铜合金	(Ni plated) 镀镍
2	(Screw) 螺丝 M3	(Steel) 钢	(Zn plated) 镀锌
1	(Housing) 罩件	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

PART NO.: /
 APPD: /
 CHKD: /
 DRFT: /

THIRD ANGLE PROJECTION

宁波迈科思电子科技有限公司
 NINGBO MAX ELECTRONIC TECHNOLOGY CO.,LTD

型号 MX2EDGKA-5.00-XXP
系列 MX2EDGKA-5.00 **页码** 1/1
图号 MX2EDGKA500001 **比例** 1:1